

Installation guideline

ConTool

Updated: 06.04.2011

Created by: consolut international ag
Ebnatstrasse 65c
CH-8200 Schaffhausen
fon: +41 (0) 525 33833 10
fax: +41 (0) 525 33833 2

info@consolut.com
www.consolut.com

Documentation path: N:\SAPWEBAS\ConTool\

Table of contents

1	Product description CONSQL	3
1.1	Download link	3
1.2	How to install I ? (on iSeries).....	3
1.3	How to install II ? (on PC).....	3
1.4	How to install III ? (on iSeries).....	4
1.5	How to install IV ConTool Diskanalyzer ? (on PC)	4
1.6	How to start the ConTool Diskanalyzer tool ?	4
1.7	How to plan via Job Scheduler (Diskanalyzer)?	5
1.8	How to use the data of the Diskanalyzer tool ?.....	5
1.9	How to use the consolut Start SAP Tool ?.....	5
1.10	How to use the consolut Stop SAP Tool ?	5
1.11	How to use the consolut DLTJRNRCV Tool ?	6
2	How to use the consolut commands ?	7
2.1	Command DSPFF.....	7
2.2	Command EDTDTAARA	7
2.3	Command CONCMP	7
2.4	Command CONSTRCRT	7
2.5	Programm CONRFCRCV.....	7
2.6	Programm CONRFCSND.....	7
2.7	Programm CONRFCSND1	7
3	Imprint	8

1 Product description CONSQL

1.1 Download link

<http://www.consolut.com/en/s/download/contool.html>

1.2 How to install I ? (on iSeries)

- Logon with QSECOFR
- CRTSAVF QGPL/CONTOOL
- CRTSAVF QGPL/CONTOOLD

1.3 How to install II ? (on PC)

- unzip the file ConTool.zip to the 2 files "contool" & "contoold" to c:\temp
- ftp the data binary to your iSeries into the created SAVFs

You can do that similar as follows:

```
ftp <iSeries-Name>  
cd qgpl  
bin  
lcd c:\temp  
put contool  
put contoold  
quit
```

1.4 How to install III ? (on iSeries)

1. Logon with QSECOFR
2. RSTLIB SAVLIB(CONTOOL) DEV(*SAVF) SAVF(QGPL/CONTOOL) MBROPT(*ALL) ALWOBJDIF(*ALL)
3. RSTLIB SAVLIB(CONTOOLD) DEV(*SAVF) SAVF(QGPL/CONTOOLD) MBROPT(*ALL) ALWOBJDIF(*ALL)
4. mkdir '/ConTool'
5. RST DEV('/QSYS.LIB/CONTOOL.LIB/CONTOOLIFS.FILE') OBJ('/ConTool/*')
6. GRTOBJAUT OBJ(CONTOOL/*ALL) OBJTYPE(*ALL) USER(*PUBLIC) AUT(*ALL)
7. GRTOBJAUT OBJ(CONTOOLD/*ALL) OBJTYPE(*ALL) USER(*PUBLIC) AUT(*ALL)
8. CALL CONTOOL/CRTSHARES
9. If you are using iASP, you need to change the DTAARA CONTOOLD/IASP as follows:
10. CHGDTAARA DTAARA(CONTOOLD/IASP) VALUE('Your-iASP')

1.5 How to install IV ConTool Diskanalyzer ? (on PC)

- Rename the file
\\<iSeries-Name>rootbin\ConTool\Data\HostSpaceOccupied.htm
with your Windows Explorer to
\\<iSeries-Name>rootbin\ConTool\Data\<iSeries-Name>SpaceOccupied.htm
- Edit the file the following file with notepad, pspad, textpad or similar and exchange all occurrences of "&HOST&" with "<iSeries-Name>" (Should be about 40 times)
\\<iSeries-Name>rootbin\ConTool\Data\<iSeries-Name>SpaceOccupied.htm

1.6 How to start the ConTool Diskanalyzer tool ?

- Logon with QSECOFR (e.g. every sunday 4pm via WRKJOBSCDE weekly)
- CALL PGM(CONTOOL/STRCONTOSM)

1.7 How to plan via Job Scheduler (Diskanalyzer)?

```
ADDJOBSCDE JOB(STRCONTOOL) CMD(CALL PGM(CONTOOL/STRCONTOSM))  
FRQ(*WEEKLY) SCDDATE(*NONE) SCDDAY(*SUN) SCDTIME(160000)  
RCYACN(*NOSBM) JOBD(CONTOOL/CONTOOL) JOBQ(QCTL)  
TEXT('Start ConTool for Disk Checks')
```

... STRCONTOSM should be modified for iASP ...

1.8 How to use the data of the Diskanalyzer tool ?

- Mount a network drive e.g. X:\ with \\<iSeries-Name>\ROOTBIN
- Start your Internet Browser and enter the following:
X:\ConTool\Data\<iSeries-Name>SpaceOccupied.htm
... click on the different links and enjoy :-))

1.9 How to use the consolut Start SAP Tool ?

- CHGOBJOWN OBJ(CONTOOL/CONSTRSAP1) OBJTYPE(*PGM) NEWOWN(QSECOFR)
- CHGPGM PGM(CONTOOL/CONSTRSAP1) USRPRF(*OWNER)
- If you want to start your SAP system include the following:
CALL PGM(CONTOOL/CONSTRSAP1) PARM(SID)

1.10 How to use the consolut Stop SAP Tool ?

- CHGOBJOWN OBJ(CONTOOL/CONENDSAP1) OBJTYPE(*PGM) NEWOWN(QSECOFR)
- CHGPGM PGM(CONTOOL/CONENDSAP1) USRPRF(*OWNER)
- If you want to stop your SAP system include the following:
CALL PGM(CONTOOL/CONENDSAP1) PARM(SID)

1.11 How to use the consolut DLTJRNRCV Tool ?

- Before the nightly backup delete all old contents:
CLRPFM FILE(CONTOOL/DLTJRNRCV)

- Run the following for each SID BEFORE the backup:
CALL PGM(CONTOOL/DLTJRNRCV1) PARM(SID)

- Run the following AFTER your backup once:
CALL PGM(CONTOOL/DLTJRNRCV2)

2 How to use the consolut commands ?

2.1 Command DSPFF

This command is better than DSPFFD

2.2 Command EDTTAARA

This command is better than CHGDTAARA for CHAR.

2.3 Command CONCMP

Useful Pre-Compile-Statements

2.4 Command CONSTRCRT

Send file and Field definition to SAP

2.5 Programm CONRFCRCV

Standard tool for RFC transfer from SAP (includes table)

2.6 Programm CONRFCSND

Standard tool for RFC transfer to SAP (includes table)

2.7 Programm CONRFCSND1

Standard tool for RFC transfer to SAP (without table)

3 Imprint

This document was created by:

consolut international ag
Ebnatstrasse 65c
8200 Schaffhausen
Switzerland

Fon : +41(0)525 33833 10

Fax : +41(0)525 33833 2

Contact: info@consolut.com

Internet: www.consolut.com